



Facestation

Call: 01623 883 073

Smart Face Recognition Terminal

Suprema FaceStation 2 is the most advanced face recognition terminal providing loads of the world's best features. Powered by Suprema's latest innovation in facial biometrics, FaceStation 2 offers unrivalled matching speed, accuracy and level of security. With Suprema's patented optic engineering, FaceStation 2 achieves up to 25,000 lx of operating illuminance which in turn, brings all-round confidence regardless of lighting conditions. Packed in an ergonomically-designed structure, FaceStation 2 provides exceptional performance and usability for diverse access control and time attendance sites, large or small.

Contact Address

Datatile Systems Ltd
1 Keepers Cottage, Hexgreave Hall Estates, Upper Hexgreave, Newark, Nottinghamshire NG22 8LS

General Enquiries
Email: info@Datatile.co.uk
Website: www.datatile.co.uk

Features

- Ultra Performance
 - Matching Speed: 1:3,000 match/sec
 - User Capacity 30,000 users
- Highest Operating Luminance
 - Operating luminance from 0 lx to 25,000 lx
 - Highest operating luminance available
 - Covers complete darkness to all indoor lighting conditions
- Expanded Capacity
 - Max 500,000 users
 - 5,000,000 text logs and 50,000 image logs
 - Large memory: 1GB RAM and 8GB Flash
- Multi RFID Card Reading
 - LF(125KHz), HF(13.56MHz) dual-band
 - Reads all card types that HID multiCLASS supports
- Ergonomics & User Convenience
 - Extended height range: 145cm – 210cm
 - Tilt-type bracket for wheelchaired persons & children
 - Android 5.0 Lollipop based intuitive GUI
 - Improved face enrolment procedure



suprema

Power	24DCV, Max 2.5A
Operating Temperature	-20° to 50°C
Operating Humidity	0%-80%, non-condensing
Max Users/Logs	30000/5,000,000
Image Dimension	720 x 480 pixels
LCD/LED	4" colour TFT LCD, 800 x 480 pixel resolution/IR 140 ea LED
Connectivity/Connections	Wi-Fi, Ethernet, RS-485, Wiegand, TTL input, Relay, USB, Tamper
Memory/CPU	8GB Flash + 1GB RAM/1.4Ghz Quad Core
Dimension (W x H x D)	141 mm (W) x 164 mm (H) x 125 mm (D)
Unit Weight	548g
Video Phone	SIP-based VoIP (video + voice)
Sound	24 bit/Voice DSP (echo cancelation)
Certificates	CE, FCC, KC, RoHS, REACH, WEEE, BT SIG
RF Card Options	EM, HID Prox, MiFare, DESFire, DesFire EV1, Felica, NFC, iClass SE

Contact Address

Datamine Systems Ltd
1 Keepers Cottage, Hexgreave Hall Estates, Upper Hexgreave, Newark, Nottinghamshire NG22 8LS

General Enquiries

Email: info@Datamine.co.uk
Website: www.datamine.co.uk